



Washdown Pumps 06

PAR-Max 3.0 GPM Washdown Pump

PAR-Max 4.0 GPM Washdown Pump

PAR-Max 7.0 GPM Ultra Washdown Pump

HotShot Series

PAR-Max Washdown Kits



06 Washdown Pumps

SELECTION GUIDE

PAR-Max 3.0 GPM Washdown Pump		Model	Details	Fitting	Size (length x width x height)	Weight	Flow Rate gpm (lpm)	Shut-Off Pressure
	32305-0092	12 volt DC model, 10 amp fuse size.	Connections for ½" or ¾" hose.		9" x 4.5" x 4.5" (23cm x 11cm x 11cm)	3.5lb (1.6kg)	3.0 (11.4)	50 psi (3.5 bar)
	32305-0094	24 volt DC model, 5 amp fuse size.						
	32305-0392	12 volt DC model, 10 amp fuse size.						
	32305-0394	24 volt DC model, 5 amp fuse size.						
	32901-0092	12 volt DC model, 10 amp fuse size with 25ft (7.6m) hose coil.						
	32901-0094	24 volt DC model, 5 amp fuse size with 25ft (7.6m) hose coil.						

PAR-Max 4.0 GPM Washdown Pump		Model	Details	Fitting	Size (length x width x height)	Weight	Flow Rate gpm (lpm)	Shut-Off Pressure
	32605-0092	12 volt DC model, fuse 15 amp.	Connections for ¾" (19mm) ID hose.		7.8" x 4.0" x 4.0" (20cm x 10cm x 10cm)	5lb (2.1kg)	4.0 (15)	60 psi (4.3 bar)
	32605-0094	24 volt DC model, fuse 10 amp.						
	32900-0092	12 volt DC model with 25ft (7.6m) hose coil.						
	32900-0094	24 volt DC model with 25ft (7.6m) hose coil.						

PAR-Max 7.0 GPM Ultra Washdown Pump		Model	Details	Fitting	Weight	Flow Rate gpm (lpm)	Shut-Off Pressure
	52700-0092	12v DC Model, 28 amp max.	Connections for ½" or ¾" hose.		6.5lb (3.0kg)	7.0 (26.5)	80 psi (5.5 bar)
	52700-0094	24v DC Model, 14 amp max.					
	52900-0092	12 volt DC model, 28 amp.					
	52900-0094	24 volt DC model, 14 amp.					

HotShot Series		Model	Details	Fitting	Size (length x width x height)	Weight	Flow Rate gpm (lpm)	Shut-Off Pressure
	82405-0092	12 volt DC.	½" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	7.6lb (3.5kg)	4 (15.1)	70 psi (4.8 bar)
	82405-0094	24 volt DC.	½" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	7.6lb (3.5kg)	4 (15.1)	70 psi (4.8 bar)
	82505-0092	12 volt DC.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	7.6lb (3.5kg)	5.0 (18.9)	70 psi (4.8 bar)
	82505-0094	24 volt DC.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	7.6lb (3.5kg)	5.0 (18.9)	70 psi (4.8 bar)
	82605-0092	12 volt DC.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	7.6lb (3.5kg)	6.0 (22.7)	70 psi (4.8 bar)
	82605-0094	24 volt DC.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	7.6lb (3.5kg)	6.0 (22.7)	70 psi (4.8 bar)
	82906-0092	12 volt DC washdown kit.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	Call for more info.	6.0 (22.7)	70psi (4.8 bar)
	82906-0094	24 volt DC washdown kit.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	Call for more info.	6.0 (22.7)	70psi (4.8 bar)
	82905-0092	12 volt DC washdown kit.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	Call for more info.	5.0 (18.9)	70psi (4.8 bar)
	82905-0094	24 volt DC washdown kit.	¾" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	Call for more info.	5.0 (18.9)	70psi (4.8 bar),
	82904-0092	12 volt DC washdown kit	½" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	Call for more info.	4 (15.1)	70psi (4.8 bar)
	82904-0094	24 volt DC washdown kit.	½" Hose Barb.		10.59" x 4.33" x 2.76" (26.9cm x 11cm x 7cm)	Call for more info.	4 (15.1)	70psi (4.8 bar)

06 Washdown Pumps

INTRODUCTION



PAR-Max 3.0 GPM Washdown Pump

- Suitable for Marine Washdown.
- Self priming up to 3m (10ft).



FLOW	3.0 gpm (11.4 lpm)
SHUT-OFF PRESSURE	50 psi (3.5 bar)
FITTING	Connections for ½" or ¾" hose.
SIZE	9" long x 4.5" wide x 4.5" high (23cm x 11cm x 11cm)
WEIGHT	3.5lb (1.6kg)

Suitable for North America:

- 32305-0092**
12 volt DC model, 10 amp fuse size.
- 32305-0094**
24 volt DC model, 5 amp fuse size.

Suitable for Worldwide:

- 32305-0392**
12 volt DC model, 10 amp fuse size.
- 32305-0394**
24 volt DC model, 5 amp fuse size.
- 32901-0092**
12 volt DC model, 10 amp fuse size with 25ft (7.6m) hose coil.
- 32901-0094**
24 volt DC model, 5 amp fuse size with 25ft (7.6m) hose coil.

PAR-Max 4.0 GPM Washdown Pump

- Suitable for high pressure applications.
- Self priming up to 10ft (3m).



FLOW	4.0 gpm (15 lpm)
SHUT-OFF PRESSURE	60 psi (4.3 bar).
FITTING	Connections for ¾" (19mm) ID hose
SIZE	7.8" long x 4.0" wide x 4.0" high (20cm x 10cm x 10cm).
WEIGHT	5lb (2.1kg)

Suitable for North America:

- 32605-0092**
12 volt DC model, fuse 15 amp.
- 32605-0094**
24 volt DC model, fuse 10 amp.
- 32900-0092**
12 volt DC model with 25ft (7.6m) hose coil.
- 32900-0094**
24 volt DC model with 25ft (7.6m) hose coil.

Suitable for Europe:

- 32605-0392**
12 volt DC model, fuse 15 amp.
- 32605-0394**
24 volt DC model, fuse 10 amp.
- 32900-0092**
12 volt DC model with 25ft (7.6m) hose coil.
- 32900-0094**
24 volt DC model with 25ft (7.6m) hose coil.

PAR-Max 7.0 GPM Ultra Washdown Pump

Step up to extreme cleaning with this seven gallon per minute, high pressure washdown system. The powerful spray makes cleaning your boat or dock faster and easier than ever. Its robust design will provide many years of reliable service. With complete instructions and an included main breaker, this washdown system can be installed on almost any size boat.

- Pump Body - Glass Fitted Nylon.
- Pump Design - 5 Chamber Diaphragm.
- Suction Lift - Self Priming to 8ft. (2.5m).
- Ports (2) - ¾" (19mm) Hose Barb (2) - ¾" (19mm) Hose Barb and Elbow.
- Motor - Permanent Magnet.
- Suitable for Marine Washdown.
- ISO 8846 MARINE (Ignition Protection).



FLOW	7.0 gpm (26.5 lpm)
SHUT-OFF PRESSURE	80 psi (5.5 bar).
FITTING	Connections for ½" or ¾" hose
WEIGHT	6.5lb (3.0kg).

- 52700-0092**
12v DC Model, 28 amp max.
- 52700-0094**
24v DC Model, 14 amp max.

- Suitable for North America:
52900-0092
12 volt DC model, 28 amp.
- 52900-0094**
24 volt DC model, 14 amp.

PAR-Max Washdown Kit

Jabsco offers boaters several washdown pumps at ideal flow and pressure for washdown. The NEW! PAR-Max 5.0 gpm Washdown model offers pressures up to 50 psi (3.5 bar) with 4 chamber smooth performance running at up to 5 gpm (19 lpm). The NEW! PAR-Max 7.0 gpm Washdown model offers an unbeatable flow rate of up to 7.0 gpm (26.5 lpm) at pressures of up to 80 psi (5.5 bar). Washdown pumps are ideal for cleaning decks, cockpits and anchors on yachts of a range of sizes and can be connected to sea or fresh water. Both NEW units come with an intake strainer, spray nozzle and quickconnect 3/4" hose barb fittings.

- High pressure jet blasts mud and silt from anchor chain and decks.
- Waterproof with sealed motor and sealed pressure switch for mounting in exposed positions.
- Thermal overload protection automatically stops the motor if it overheats.
- Dry running.
- Soft rubber mounts.
- Corrosion resistant.
- Complies with USCG 183.410 and ISO 8846 MARINE (Ignition Protection).
- Supplied complete with Pumpgard™ and trigger nozzle.



Parts for PAR-Max Washdown
(* or ** indicates which model is in the kit)

30703-1000 Quick-disconnect nozzle with 3/4" GHT snap-in connector (Suitable for North America)*. 24 volt DC washdown kit.	46400-0002 Pumpgard™ Strainer (Suitable for Europe)**.
30704-1000 Quick-disconnect nozzle attaches permanently to 1/2" hose. (Suitable for Europe)**.	31911-0000 Deck fitting, 1/2" NPT female inlet with one 3/4" GHT male hose adaptor.
46400-0000 Pumpgard™ Strainer (Suitable for North America)*.	31911-0007 Deck fitting, 1/2" BSP female inlet, with one 3/4" BSP male hose adaptor.

HotShot Series

The new HotShot Series robust five chamber, patented co-injected moulded diaphragm and larger heavier duty motor brushes significantly extends pump life by up to 50%. The HotShot Series washdown pumps are available in 4.0 (15.1 lpm), 5.0 (18.9 lpm) and 6.0 GPM (22.7 lpm) with pressures up to 70 PSI (4.8 bar) and are selfpriming up to 10ft. (3m).

- Sealed switch and co-moulded diaphragm, eliminates leak paths, extending the life of the pumps by up to 50%.
- Ergonomically designed spray nozzle provides powerful and accurate fire power with every shot.
- Quick Disconnect Ports allow for adjustable and ease of installation.
- Kits include spray nozzle, fitting, Pumpgard strainer and hose.
- Improved Noise Dampening Rubber Feet, significantly minimizes vibration when mounted against hard surfaces.
- Available in 12 or 24 VDC.
- Certified to EN ISO 8846 Marine (Ignition Protection).



FLOW	4.0 (15.1 lpm), 5.0 (18.9 lpm) and 6.0 GPM (22.7 lpm)
SHUT-OFF PRESSURE	80 psi (5.5 bar).
FITTING	1/2" Hose Barb on 4 gpm. 3/4" Hose Barb on 5.0 and 6.0 gpm.
SIZE	26.9cmx11cmx7cm
WEIGHT	7.6lb (3.5kg) 5.0 and 6.0gpm models

82405-0092 70 psi (4.8 bar), 4.0 gpm (15.1 lpm), 12 volt DC.	82906-0092 82906-0092 70psi (4.8 bar), 6 gpm (22.7 lpm), 12 volt DC washdown kit.
82405-0094 70 psi (4.8 bar), 4.0 gpm (15.1 lpm), 24 volt DC.	82906-0094 70psi (4.8 bar), 6 gpm (22.7 lpm), 24 volt DC washdown kit.
82505-0092 70 psi (4.8 bar), 5.0 gpm (18.9 lpm), 12 volt DC.	82905-0092 70psi (4.8 bar), 5 gpm (18.9 lpm), 12 volt DC washdown kit.
82505-0094 70 psi (4.8 bar), 5.0 gpm (18.9 lpm), 24 volt DC.	82905-0094 70psi (4.8 bar), 5 gpm (18.9 lpm), 24 volt DC washdown kit.
82605-0092 70 psi (4.8 bar), 6.0 gpm (22.7 lpm), 12 volt DC.	82904-0092 70psi (4.8 bar), 4 gpm (15.1 lpm), 12 volt DC washdown kit.
82605-0094 70 psi (4.8 bar), 6.0 gpm (22.7 lpm), 24 volt DC.	82904-0094 70psi (4.8 bar), 4 gpm (15.1 lpm), 24 volt DC washdown kit.